

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problems Mailbox.**

R 232 N 100  
all set + no check self



(11) Publication number: **0 483 994 A1**

(12) **EUROPEAN PATENT APPLICATION**

(21) Application number: **91309442.1**

(51) Int. Cl.<sup>5</sup>: **E06B 9/386**

(22) Date of filing: **15.10.91**

(30) Priority: **17.10.90 JP 108756/90 U**  
**19.10.90 JP 281108/90**  
**05.11.90 JP 116042/90 U**

(43) Date of publication of application:  
**06.05.92 Bulletin 92/19**

(64) Designated Contracting States:  
**DE FR GB IT NL**

(71) Applicant: **KABUSHIKI KAISHA NICHIBEI**  
**3-15-4, Nihonbashi**  
**Chuo-ku Tokyo (JP)**

(72) Inventor: **Kataoka, Mamoru, c/o Kabushiki**  
**Kaisha Nichibei**  
**3-15-4, Nihonbashi**  
**Chuo-ku, Tokyo (JP)**

Inventor: **Yamanaka, Hiroomi, c/o Kabushiki**  
**Kaisha Nichibei**  
**3-15-4, Nihonbashi**  
**Chuo-ku, Tokyo (JP)**  
Inventor: **Sone, Akira, c/o Kabushiki Kaisha**  
**Nichibei**

**3-15-4, Nihonbashi**  
**Chuo-ku, Tokyo (JP)**  
Inventor: **Saitoh, Kenichi, c/o Kabushiki**  
**Kaisha Nichibei**

**3-15-4, Nihonbashi**  
**Chuo-ku, Tokyo (JP)**  
Inventor: **Yamagishi, Masaaki, c/o Kabushiki**  
**Kaisha Nichibei**  
**3-15-4, Nihonbashi**  
**Chuo-ku, Tokyo (JP)**  
Inventor: **Yoshida, Shirochiro, c/o Kabushiki**  
**Kaisha Nichibei**  
**3-15-4, Nihonbashi**  
**Chuo-ku, Tokyo (JP)**

(74) Representative: **Beresford, Keith Denis Lewis**  
**et al**  
**BERESFORD & Co. 2-5 Warwick Court High**  
**Holborn**  
**London WC1R 5DJ (GB)**

(54) **Blind.**


(57) There is disclosed a blind which includes a head box, ladder-shaped supporting cords (2) vertically extending from a bottom of said head box, a plurality of horizontal slats (3) supported by said ladder-shaped supporting cords (2) in vertically spaced relation to each other, a bottom rail (5) disposed at the bottom of said plurality of horizontal slats (3), and lifting cords (4) for raising or lowering said plurality of horizontal slats (3), each lifting cord (4) vertically extending from the bottom of the head box through cord passing holes formed in the respective slats (3) and being connected, at its lower end, to said bottom rail (5), wherein the slats (3) are arranged to be raised or lowered by means of the lifting cords (4) and to be tilted by means of said ladder-shaped supporting cords (2) in order to adjust light-shielding effect of the blind. In one form of the invention, each of said slats (3) has an angle-shape in section; each of said cord passing holes is formed as a slot which extends from an apex portion of said angle-shape toward one side edge of said slat (3); and the position of said lifting cord (4) coming out from the bottom of the head box is located aside of a center line of the bottom of

the head box toward said one side edge. In the other form, each of said slats (3) has a first part extending from an apex portion of said angle-shape to one side edge of said slat and a second part extending from the apex portion of said angle-shape to the other side edge of the slat, said first part being porous and semi-light-transmitting and said second part being non-porous and non-light-transmitting and said cord passing hole is formed at the apex portion of said slat (3).

In the preferred form, each of the slats (3) has an angle-shape in section including an apex and two side parts slanting from the apex to both side edges of the slat, and each of the horizontal portions of the ladder-shaped supporting cords (2) has a length which is substantially equal to a sum of widths of the two side parts from the apex to the both side edges of the slat (3).

EP 0 483 994 A1

FIG.5



# Background of the Invention:

## Field of the Invention:

The present invention relates to a blind which includes a head box, ladder-shaped supporting cords vertically extending from a bottom of said head box, a plurality of horizontal slats supported by said ladder-shaped supporting cords in vertically spaced relation to each other, a bottom rail disposed at the bottom of said plurality of horizontal slats, and lifting cords for raising or lowering said plurality of horizontal slats, each lifting cord vertically extending from the bottom of the head box through cord passing holes formed in the respective slats and being connected, at its lower end, to said bottom rail, wherein the slats are arranged to be raised or lowered by means of the lifting cords and to be tilted by means of said ladder-shaped supporting cords in order to adjust light-shielding effect of the blind.

## Description of the Prior Art:

Recently, in the field of the blind of this kind, there has been developed a blind in which each of the slats has an angle-shape in section and the cord passing hole is formed at an apex portion of said angle-shape. Figs. 1 and 2 illustrates an example of the blind of this kind. In Figs. 1 and 2, 1 designates a slat having an angle-shape in section, and 2 designates a cord passing hole for passing a lifting cord therethrough which is formed at an apex portion of said angle-shape. As shown in Fig. 3, a plurality of such slats 1 are supported by means of ladder-shaped supporting cords 4 which vertically extend from a bottom of a head box 3 downwardly. Each of lifting cords 5 for raising or lowering the slats comes out from a center position of the bottom of the head box 3 and extends through the cord passing holes 2 formed in the respective slats 1. The lifting cord 5 is connected, at its lower end, to a bottom rail 6 disposed at the bottom of the plurality of slats 1. These slats 1 are arranged to be raised or lowered by pulling the lifting cords 5 into or out of the head box 3 and to be tilted by relatively moving front and rear cord portions of the ladder-shaped supporting cords in vertical direction, thereby adjusting light-shielding effect of the blind.

In the blind including the slats having the angle-shape in section, when the slats are tilted by the ladder-shaped supporting cords, as explained above, the inner edges of the cord passing holes formed in the respective slats come into contact with the lifting cords, thereby hindering the tilting action of the slats so that it is difficult to tilt the slats to the desired vertical positions.

In the conventional blind of this type, slats having arcuate-shape in section have been usually used. The inventors have recently developed a new type of

blind which includes arcuate-shaped slats, each of which is formed with many small pores, thereby forming a semi-light-transmitting slat (which is called as a "punched slat"). The blind using the punched slats of this type has such characteristic feature that when the blind is completely closed by tilting the slats to their vertical positions, the outside can be seen from the inside of a room while shielding a sun light, that is very convenient in practical use and this blind presents a superior external appearance. This blind has a good reputation for such characteristic feature, but has such defect that when the outside becomes dark, while the inside of the room is light, it is difficult to completely keep the inside of the room out of sight from the outside. This blind has a further defect in that a cord passing a hole for passing a lifting cord is relatively large and it is difficult to completely avoid the leakage of light through the cord passing hole.

## Summary of the Invention:

It is an object of the present invention to provide a blind using slats of angle-shape in section, in which the slats can be fully tilted to the vertical positions, without being subjected to the hindering action of the lifting cords coming into contact with the edges of the cord passing holes formed in the slats.

It is another object of the present invention to provide a blind which avoids the defects of the blind using the semi-light-transmitting punched slats, which the inventors have previously developed, as described above and to provide a blind which can be changed to a semi-light-transmitting blind and a non-light-transmitting blind.

It is another object of the present invention to provide a blind which can completely avoid leakage of light through cord passing holes when the blind is completely closed.

It is a further object of the present invention to provide a horizontal blind in which slats having angle-shape in section are used, which is arranged to enable folding of the slats to the position where the slats come into intimate contact with each other and which enables to fully open the blind slats.

In accordance with the present invention, there is provided, a blind including a head box, ladder-shaped supporting cords vertically extending from a bottom of said head box, a plurality of horizontal slats supported by said supporting cords in vertically spaced relation to each other, a bottom rail disposed at the bottom of said plurality of horizontal slats and lifting cords for raising or lowering the plurality of slats, each lifting cord vertically extending from the bottom of the head box through cord passing holes formed in the respective slats and being connected, at its lower end, to said bottom rail, wherein the slats are arranged to be raised or lowered by means of said lifting cords and to be tilted by means of said ladder-shaped support-

ing cords in order to adjust light-shielding effect of the blind, characterized in that each of said slats has an angle-shape in section; each of said cord passing holes is formed as a slot which extends from an apex portion of said angle-shape toward one side edge of said slat; and the position of said lifting cord coming out from the bottom of the head box is located aside of a center line of the bottom of the head box toward said one side edge.

Further, in accordance with the present invention, there is provided a blind of this type, characterized in that each of said slats has an angle-shape in section; each slat has a first part extending from an apex portion of said angle-shape to one side edge of said slat and a second part extending from the apex portion of said angle-shape to the other, side edge of the slat, said first part being porous and semi-light-transmitting, said second part being non-porous and non-light-transmitting; and the cord passing holes are formed at the apex portion of said slat.

In accordance with an embodiment of the invention, there is provided a blind wherein said cord passing hole is formed as a slot which extends from the apex portion of said angle-shape to the first portion of the slat at substantially right angle to the slat.

In accordance with another embodiment of the invention, there is provided a blind wherein said cord passing hole is formed as a slot which extends from the apex portion of said angle-shape to the second part of the slat at substantially right angle to the slat.

In accordance a further embodiment of the invention, there is provided a blind wherein the position of the lifting cord coming out from the bottom of the head box is located aside of a center line of the bottom of the head box toward the same side as that of the slat where said slot is formed.

Further in accordance with the present invention there is provided a horizontal blind including a plurality of horizontal slats supported in vertically spaced relation to each other by means of ladder-shaped supporting cords, each having a front vertical cord portion, a rear vertical cord portion and horizontal cord portions connecting said front and rear vertical cord portions at vertically spaced positions, characterized in that each of the slats has an angle-shape in section including an apex and two side parts slanting from the apex to both side edges of the slat, and each of the horizontal portions of the ladder-shaped supporting cords has a length which is substantially equal to a sum of widths of the two side parts from the apex to the both side edges of the slat.

#### Brief Description of the Drawings:

Fig. 1 is a perspective view showing a blind according to a prior art.

Fig. 2 is a perspective view showing a slat used in the blind shown in Fig. 1.

Fig. 3 is a side view of the blind shown in Fig. 1.

Fig. 4 is a perspective view of a slat according to an embodiment of the present invention.

Fig. 5 is a side view of the blind in which the slats shown in Fig. 4 are used.

Fig. 6 is a perspective view showing another embodiment of the present invention.

Fig. 7 is a perspective view showing the slat according to another embodiment of the present invention.

Fig. 8 is a side view of the blind shown in Fig. 6.

Fig. 9 is a perspective view showing a slat according to another embodiment of the present invention.

Fig. 10 is a side view of the blind in which the slats shown in Fig. 9 are used.

Fig. 11 is a plan view of the slat according to a further embodiment of the present invention.

Fig. 12 is a perspective view showing a slat according to another embodiment of the invention.

Fig. 13 is a side view of the blind in which the slats shown in Fig. 12 are used.

Fig. 14A and 14B illustrate a ladder-shaped supporting cord according to a prior art.

Fig. 15A and 15B illustrate a ladder-shaped supporting cord according to the present invention.

#### Detailed Description of the Preferred Embodiment:

Now the explanation will be given to the preferred embodiments of the invention as illustrated in the drawings.

Fig. 1 illustrates the horizontal blind. The blind shown in the drawings includes a head box 1, ladder-shaped supporting cords 2, a plurality of horizontal slats 3 supported in vertically spaced relation by means of said supporting cords, lifting cords 4 for raising or lowering the slats, a bottom rail 5 arranged at the bottom of the plurality of horizontal slats and an operating cord 6 for effecting raising or lowering operation as well as slat tilting operation.

As shown in Fig. 2, a cord passing hole 7 for passing a lifting cord therethrough is formed at an apex of said angle-shape.

As shown in Fig. 3, a plurality of such slats 3 are supported by means of ladder-shaped supporting cords 2 which vertically extend from a bottom of a head box 1 downwardly. Each of lifting cords 4 for raising or lowering the slats comes out from a center position of the bottom of the head box 1 and extends through the cord passing holes 7 formed in the respective slats 3. The lifting cord 4 is connected, at its lower end, to a bottom rail 5 disposed at the bottom of the plurality of slats 3. These slats 3 are arranged to be raised or lowered by pulling the lifting cords 4 into or out of the head box 1 and to be tilted by relatively moving front and rear cord portions of the ladder-shaped supporting cords 2 in vertical direction, thereby adjusting light-shielding effect of the blind.

In the blind including the slats having the angle-shape in section, when the slats are tilted by the ladder-shaped supporting cords, as explained above, the inner edges of the cord passing holes 7 formed in the respective slats come into contact with the lifting cords 4 thereby hindering the tilting action of the slats, so that it is difficult to tilt the slats to the desired vertical positions. In order to eliminate such defect, the present invention provides a blind in which each of said cord passing holes 7 is formed as a slot which extends from an apex portion of said angle-shape toward one side edge of said slat and the position of said lifting cords coming out from the bottom of said head box 1 is located aside of a center line of said bottom of the head box 1 toward said one side edge.

According to this construction, the cord passing hole is formed a slot which extends from an apex portion of the angle-shape of the slat toward one side edge of the slat and the position of each lifting cord coming out from the bottom of the head box is located aside of the center line of the head box toward said one side edge. Accordingly, when the slat is tilted to the position where a side of the slat opposite to that of the slat comes to a vertical state, the lifting cords enter into the slots so that no hindering effect can occur by the lifting cords coming into contact with the inner edges of the slats. Thus it is possible to tilt the slats to their completely vertical positions. Furthermore, the cord passing hole is formed from the apex portion of the slat toward only one side thereof, so that leakage of a light through the cord passing holes at the vertically tilted state of the slats can be completely avoided.

Such embodiment is illustrated in Figs. 4 and 5.

The cord passing hole 7 is formed as a slot which extends from the apex portion of the angle-shaped slat 3 toward one side edge of the slot. The position of the lifting cord 4 coming out from the bottom of the head box is located aside of the center line of the bottom of the head box toward one side edge of the slat, as shown in Fig. 5. Accordingly, when the slat is tilted in the direction opposite to the side where the slot is formed, the slat can be tilted, without being subjected to hindrance caused by the cord coming into contact with the inner edge of the slot. Furthermore, substantially no hole is formed in the side of the slat opposite to the side where the slot is formed, so that the leakage of light through the cord passing is avoided.

Accordingly, the slats can be tilted to their completely light-shielding state and the leakage of light through the cord passing holes can be completely avoided.

Fig. 6 illustrates another embodiment of the blind according to the present invention. The embodiment shown in Fig. 1 includes same parts as those shown in Fig. 1. In the constructions of the illustrated blind, an actuator rod (not shown) arranged in the head box is rotated by the operating cord 6, whereby the slats

3 are raised or lowered through the lifting cords 4 and the slats 3 are tilted to one or other direction through the ladder-shaped supporting cords 2. The operating mechanism is well known in the art of the blind of this kind and, therefore, the detailed description thereof is omitted.

The slat 3 has an angle-shape in section, as shown in Fig. 7, and has a first part 3a extending from an apex portion of said angle-shape to one side edge of the slat, said first part being porous and semi-light-transmitting, and a second part 3b extending from the apex portion of said angle shape to the other side edge of the slat, said second part being non-porous and non-light-transmitting. The cord passing hole 7 is formed in the apex portion of the slat. The tilted state of the slat is shown in Fig. 8.

In this construction, when the blind is operated to the position where the first parts 3a of the slats 3 come to the vertical positions, the semi-light-transmitting portions 3a are aligned in the vertical position at the closed state of the blind, so that semi-light-transmitting blind is formed in the same manner as in the above-mentioned blind using the punched slats. On the other hand, when the blind is operated to the position where the second parts 3b of the slats come to the vertical positions, the non-light-transmitting portions are aligned in the vertical position at the closed state of the blind, so that the sight from the outside is completely shielded.

That is, this blind is arranged to be changed to the semi-light-transmitting state or the non-light-transmitting state by rotating the slats in one or the other direction.

In this blind, the cord passing hole 7 is relatively large, so that the leakage of the light through the cord passing holes occurs at the blind closed state.

In order to eliminate such defect, the present invention provides the blind of the above type, in which the cord passing hole 7 is formed as a slot which extends from the apex portion of the angle-shape to the first part 3a of the slat at substantially right angle thereto. Such embodiment is shown in Fig. 9.

In this embodiment, there is substantially no portion of the cord passing holes 7 in the second parts of the slats, so that when the slats are rotated to the positions where the second parts 3b are vertically aligned, the leakage of light through the cord passing holes can be avoided.

The slat having the angle-shape in section is superior in its light-shielding effect to the conventional arcuate-shape in section at the completely closed state of the blind. In fact, the blind having the conventional slats of the arcuate-shape in section cannot be closed to the position where the adjacent upper and lower slats come into direct contact, at their side edges with each other, in the completely closed state of the blind, and some clearance necessarily exists

between the lower side edge of the upper slat and the upper side edge of the lower slat. On the other hand, the blind having the slats of the angle-shape in section can be closed to the position where the adjacent upper and lower slats come into such relation that the side edge of the upper slat directly contacts with the apex portion of the lower slat, with an intermediate cord portion 8 (shown in Fig. 13) of the ladder-shape supporting cord being positioned between said adjacent slats. Thus the leakage of light through the gap between the upper and lower slats can be avoided.

However, in the case where the cord passing hole 7 is located at the center position of the slat, when the blind is operated to the completely closed position, the cord passing hole 7 comes to the overlapping position of the upper and lower slats to form the gap between the slats, with the result that the leakage of light occurs through such gap. In order to completely avoid the leakage of light, the present invention provides a construction of the blind in which the cord passing hole is formed in the semi-light-transmitting part which extends from the apex portion of the angle-shape to one side edge of the slat. According to this construction, when the blind is completely closed, the cord passing hole is concealed by the slat located thereon to avoid the leakage of light, so that the complete light-shielding effect is obtained.

In the case where the slat is tilted in the opposite direction, the cord passing hole is exposed to large extent, so that the light-shielding effect can be obtained only when the slats are rotated in one direction. However, the cord passing hole is formed at the side of the semi-light-transmitting part and, therefore, the leakage of light through the cord passing hole does not offer any significant problem.

Thus it is possible to effect fine adjustment of light at the blind closed state, between the completely light shielding state at the non-light-intermitting side of the slat and the semi light shielding state at the semi-light-transmitting side of the slat.

If the position of the lifting cord 4 coming out from the bottom of the head box 1 is located aside of the center line of the bottom of the head box toward the side of the slat where the slot is formed, that is, at the same side as that of the part 3a, the slats can be tilted to the state where the second parts 3b come to completely vertical positions. Thus the shielding effect of the blind can be further improved.

In the above-described embodiment, the openings of the pores appear at the edge of the lifting cord passing hole 7, as shown in Fig. 11, that is, the edge of the cord passing hole 7 forms a serrated edge. If such serrated edge is formed, the lifting cord and/or the intermediate cord portion 8 of the ladder-shaped supporting cord may be cut by the contact with such serrated edge. In order to avoid such defect, the present invention provides the blind of this type in which the cord passing hole is formed as a slot which

extends from the edge portion of the angle-shape of the second part 3b at substantially right angle thereto. Such embodiment is shown in Fig. 12.

According to this embodiment, the cord passing hole 7 is formed as a slot which extends from the apex portion of the slat to the non-light-transmitting part 3b, so that the cord passing hole is concealed by the slat located upside thereof, whereby the light leakage is avoided. That is, the homogeneous light transmitting property throughout the semi-light-transmitting parts is obtained. (however, in the case where the slats are rotated in the opposite direction, the cord passing holes are exposed to large extent and, therefore, the direction of rotation to completely shield the leakage of light through the cord passing holes is limited to one direction). In the case where the cord passing hole is formed at the center portion of the slat, as in the conventional blind, some of the pores may appear at the edge of the cord passing hole and the lifting cord and/or the intermediate cord portion of the ladder-shaped supporting cord are subjected to wearing or cutting action by the serrated edge of the cord passing hole until the lifting cord and/or the intermediate cord portion of the supporting cord become cut. As compared thereto, in the case where the cord passing hole is formed only in the non-light-transmitting side of the slat, no serrated edge is formed, so that the cutting of the cord is avoided.

In this case, it is preferred that the position of the lifting cord 4 coming out from the bottom of the head box 1 be located aside of the center of the head box toward that of the second part 3b of the slat, whereby the tilting of the slat can be effected in easier manner.

Figs. 14A and 15A illustrate the ladder-shaped supporting cord. As shown in these figures, the ladder-shaped supporting cord 2 includes front and rear vertical cord portions 2a and horizontal cord portions 2b which connect the vertical cord portions 2a at vertically spaced positions. Each slat 3 is supported on each of the horizontal cord portions. The slat 3 has an angle-shape in section, as shown in Fig. 14A, and includes an apex 3a and both side portions 3b and 3c slanting from the apex to the both side edges of the slat.

In the horizontal blind in which the slats 3 of the angle-shape in section are used, if the length of the ladder-shaped supporting cord 2b is made substantially equal to the width of the slat, as shown in Fig. 14A, when the slats have been folded upwardly, the apex of the slat comes into engagement with the horizontal cord portion of the supporting cord of the upper slat, thereby hindering the slats from being completely folded together until the slats come into intimate contact with each other.

In order to avoid such defect, according to the present invention, the length of the horizontal portion of the ladder-shaped supporting cord is made to be substantially equal to a sum of widths W1 and W2 of

the two slanting side parts 3b and 3c from the apex 3a to the both side edges of the slat, as shown in Fig. 15A. According to such arrangement, when the slats have been folded upwardly, the apex of each slat acts to upwardly push the horizontal cord portion of the upper slat, as shown in Fig. 15B, thereby folding the slats until the slats come into intimate contact with each other.

#### Claims

1. A blind, comprising:
  - a head box;
  - ladder-shaped supporting cords vertically extending from a bottom of said head box;
  - a plurality of horizontal slats supported by said supporting cords in vertically spaced relation to each other;
  - a bottom rail disposed at the bottom of said plurality of horizontal slats;
  - lifting cords for raising or lowering the plurality of slats, each of said lifting cords vertically extending from the bottom of said head box through cord passing holes formed in the respective slats and being connected, at its lower end, to said bottom rail;
  - each of said slats having an angle-shape in section;
  - each of said cord passing holes being formed as a slot which extends from an apex portion of said angle-shape toward one side edge of said slat; and
  - said lifting cord being so arranged that the position of said lifting cord coming out from the bottom of the head box is located aside of a center line of the bottom of the head box toward said one side edge.
2. A blind, comprising:
  - a head box;
  - ladder-shaped supporting cords vertically extending from a bottom of said head box;
  - a plurality of horizontal slats supported by said supporting cords in vertically spaced relation to each other;
  - a bottom rail disposed at the bottom of said plurality of horizontal slats;
  - lifting cords for raising or lowering the plurality of slats, each of said lifting cords vertically extending from the bottom of said head box through cord passing holes formed in the respective slats and being connected, at its lower end, to said bottom rail;
  - each of said slats having an angle-shape in section;
  - each of said slats having a first part extending from an apex portion of said angle-

shape to one side edge of said slat and a second part extending from the apex portion of said angle-shape to the other side edge of the slat, said first part being porous and semi-light-transmitting and said second part being non-porous and non-light-transmitting; and

said cord passing hole being formed at the apex portion of said slat.

3. A blind according to claim 2, wherein said cord passing hole is formed as a slot which extends from the apex portion of said angle-shape to the first portion of the slat at substantially right angle to the slat.
4. A blind according to claim 2, wherein said cord passing hole is formed as a slot which extends from the apex portion of said angle-shape to the second part of the slat at substantially right angle to the slat.
5. A blind according to claim 3 or 4, wherein the position of the lifting cord coming out from the bottom of the head box is located aside of a center line of the bottom of the head box toward the same side as that of the slat where said slot is formed.
6. A blind according to claim 1 or 2, wherein each of the slats has an angle-shape in section including an apex and two side parts slanting from the apex to both side edges of the slat, and each of the horizontal portions of the ladder-shaped supporting cords has a length which is substantially equal to a sum of widths of the two side parts from the apex to the both side edges of the slat.



FIG.1




FIG.2




FIG.3




FIG.4





FIG.5






FIG.8




FIG.7




FIG.9




FIG.10




FIG.11




FIG.12




FIG.13




FIG.14A




FIG.14B




FIG.15A





FIG.15B





European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number

EP 91 30 9442

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
X	CH-A-534 801 (BAUMANN & CO) * column 2, line 34 - line 40; figures *	1	E06B9/386
Y	---	3-5	
X	US-A-2 155 985 (WATERMAN) * page 1, right column, line 32 - page 2, left column, line 12; figures *	2, 6	
Y	---	3-5	
A	US-A-4 893 667 (DUNN) * column 3, line 52 - column 4, line 36; figures *	2	
A	DE-A-2 501 147 (EHAGE JALOUSIE FABRIK ERICH HINNENBERG) * page 8, paragraph 2 - page 9, paragraph 1 * * page 10, paragraph 1; figures *	1	
A	DE-A-1 779 255 (GAL GMBH & CO KG) * page 7, paragraph 2; figures *	1	
-----			
			TECHNICAL FIELDS SEARCHED (Int. Cl.5)
			E06B
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 07 FEBRUARY 1992	Examiner KUKIDIS S.
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons A : member of the same patent family, corresponding document			

EPO FORM 1503 (12.92) (P0601)